



⑪ Publication number: **0 685 845 A2**

⑫ **EUROPEAN PATENT APPLICATION**

⑲ Application number: 95302502.0

⑤① Int. Cl.⁶: **G11B 27/32, G06F 17/30, G11B 27/10, G11B 19/02**

⑳ Date of filing: 13.04.95

- ③① Priority: 14.04.94 JP 76194/94
15.03.95 JP 55970/95
- ④③ Date of publication of application:
06.12.95 Bulletin 95/49
- ⑧④ Designated Contracting States:
DE FR GB NL
- ⑦① Applicant: **KABUSHIKI KAISHA TOSHIBA**
72, Horikawa-cho,
Saiwai-ku
Kawasaki-shi, Kanagawa-ken 210, Tokyo (JP)
- ⑦① Applicant: **TOSHIBA AVE CO., LTD**
3-3-9, Shinbashi
Minato-ku, Tokyo 105 (JP)


- ⑦② Inventor: Taira, Kazuhiko, c/o K.K. Toshiba
1 1, Shibaura 1-chome,
Minato-ku
Tokyo (JP)
Inventor: Mimura, Hideki, c/o K.K. Toshiba
1 1, Shibaura 1-chome,
Minato-ku
Tokyo (JP)
Inventor: Kikuchi, Shinichi, c/o K.K. Toshiba
1 1, Shibaura 1-chome,
Minato-ku
Tokyo (JP)
Inventor: Kitamura, Tetsuya, c/o K.K. Toshiba
1 1, Shibaura 1-chome,
Minato-ku
Tokyo (JP)
- ⑦④ Representative: **Maury, Richard Phillip**
MARKS & CLERK,
57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)

⑤④ Recording medium and reproducing apparatus thereof.

⑤⑦ In a PVD table of a management region on the disc, a disc identifier 1 that represents the type of the data recording format of the disc, a number-of-disc-sides identifier 2 that represents whether the disc is a single-sided disc or a double-sided disc, and a disc side identifier 3 that represents whether the reproducing disc is side A or side B of a double-sided disc. A disc identifier 4 that represents the type of the data recording format of the file is recorded in a file (n) table including management information of the file. The reproducing apparatus reads the disc identifiers 1 and 4 from the PVD table and the file (n) table and determines whether or not the disc and the file are reproducible. In addition, the reproducing apparatus reads the number-of-disc-sides identifier 2 from the PVD table and determines whether or not the disc is a double-sided disc or a single-sided disc. When the disc is a double-sided disc, the reproducing apparatus determines whether the reproducing side is side A or side B.

FIG. 1

PHYSICAL SECTOR SIZE: 1024 BYTES
LOGICAL SECTOR SIZE: 2048 BYTES
LOGICAL BLOCK SIZE: 1024 BYTES



DISC STRUCTURE

EP 0 685 845 A2

The present invention relates to a recording medium such as an optical disc and a reproducing apparatus thereof.

Generally, management information is recorded on an optical disc. The management information manages data (files) recorded on the optical disc. As a representative example, management information defined as ISO-9660 standard is known. The management information includes at least ID information and the size of each disc, the number and reproducing order of discs that correlate, and the ID information, the record position, and the size of each file recorded on the disc as structural elements.

However, in recent years, discs that have the management information corresponding to the ISO-9660 standard are categorized as various types such as specific discs, single-sided discs, and double-sided discs. However, the conventional management information does not include information that distinguishes such disc types.

The management information is especially important for system operation. In other words, if the management information is damaged, the entire information on the disc will be lost. To prevent such a trouble, the same management information is recorded in another region as a spare. To further improve the safety of the management information, as shown in Fig. 40, the spare management information is multiplexedly recorded at multiple regions on the disc. However, in this case, the spare management information is multiplexedly recorded at a different record position. Thus, each information should have a different value that represents the position thereof. Thus, as the number of regions of the spare management information is increased, the work load of the disc provider increases.

Moreover, in recent years, as the storage capacity of optical discs increases, discs that record a plurality of stories with slightly different contents and that reproduce any story selected by the user are known. However, in this case, since the same data for each story is multiplexedly recorded, the efficiency of the disc storage capacity is remarkably low.

Furthermore, in recent years, as a technique for selectively reproducing a variety of data recorded on the disc, menus are used. When menus are composed, for example, as shown in Fig. 41, a menu list and memory image information are recorded at predetermined regions of the disc. In the menu list, the record position of menu image information corresponding to each menu number and the file record position corresponding to each menu selection number are recorded. When any menu number is selected (at step 1), a corresponding menu image information is read (at step 3) based on an address on the menu list (at step 2). Thus, the menu screen is displayed. When any file number is selected from the menu screen (at step 4), the record position of the desired

file is determined corresponding to the menu list (at step 5) and thereby the desired file is reproduced (at step 6).

However, in the method using the menu list, as the number of selection items increases, the size of the menu list increases and thereby the ratio of the data amount of the menu to the entire record data amount increases, thereby lowering the efficiency of the disc storage capacity.

A first object of the present invention is to provide a recording medium and a reproducing apparatus thereof that can determine the types of a recording medium and individual files corresponding to a data record format.

A second object of the present invention is to provide a recording medium and a reproducing apparatus thereof that determine the number of recording sides and a recording surface thereof.

A third object of the present invention is to provide a recording medium that does not need to change values that represent positions of regions of spare management information multiplexedly recorded.

A fourth object of the present invention is to provide a recording medium and a recording medium reproducing apparatus that does not need to multiplexedly record the same data.

A fifth object of the present invention is to provide a recording medium and a reproducing apparatus thereof that do not increase the ratio of menu data amount to the entire data amount even if the number of menu selection items increases.

To accomplish such objects, a first aspect of the present invention is a recording medium, comprising: a data region in which data is recorded as a file corresponding to a predetermined data recording format, and a management region including medium identifying information that represents the type of the data recording format and file identifying information that represents the type of the data recording format of the file.

A second aspect of the present invention is a reproducing apparatus, comprising a first determining means for reading medium identifying information recorded in the management region and determining a type based on a data recording format of the recording medium corresponding to the medium identifying information, and a second determining means for reading the file identifying information of each file recorded in the management region and determining a type based on the data recording format of each file recorded on the recording medium corresponding to the file identifying information.

Thus, according to the present invention, the type of the recording format for a recording medium and files can be determined. Consequently, a recording medium and files dedicated for a specific system can be accomplished.

A third aspect of the present invention is a record-

ing medium having two opposite sides, either or both of which are selective as recording sides, comprising a data region in which data is recorded, and a management region including number-of-recording-sides identifying information that represents the number of recording sides of the recording medium and recording side identifying information that represents the recording side.

A fourth aspect of the present invention is a reproducing apparatus, comprising a number-of-recording-sides determining means for reading the number-of-recording-sides identifying information recorded in the management region and determining the number of recording sides of the recording medium, and a recording-side determining means for reading the recording-side identifying information recorded in the management region and determining the recording side of the recording medium to be reproduced.

Thus, according to the present invention, different types of recording mediums that are for example single-sided type and double-sided type can be handled.

A fifth aspect of the present invention is a recording medium, comprising a data region in which data is recorded, a management region in which management information is recorded, the management information being adapted for managing data recorded in the data region, and a plurality of spare management regions in which management information with the same content as the management region is recorded, values representing the positions in the spare management regions being represented with relative distance from the top addresses thereof.

Thus, it is not necessary to change the value that represents the position of each management information.

A sixth aspect of the present invention is a recording medium on which data is recorded as a file, the file comprising a first region in which a data unit group that is a group of a plurality of types of data that are synchronously reproduced, a second region in which at least one cell information table that is a program cell composed by selectively linking at least one data unit recorded in the first region, and a third region in which at least one chain information that is a program chain composed by selectively linking at least one cell information table recorded in the second region.

A seventh aspect of the present invention is a reproducing apparatus comprising a first searching means for searching any chain information table recorded in the third region, a second searching means for searching at least one cell information table that composes the program chain from the second region corresponding to the searched chain information table, and a third searching means for searching at least one data unit that composes the program cell from the first region corresponding to the cell information table searched by the second searching means.

Thus, according to the present invention, the same program cell can be shared with a plurality of program chains. Consequently, the same data can be prevented from being redundantly recorded. As a result, the efficiency of the recording capacity of the recording medium can be maximally improved.

An eighth aspect of the present invention is a recording medium, wherein the file includes at least one cell information table that composes a menu screen on which any data item to be displayed is selected, and wherein the cell information table that composes the menu screen includes identifying information that represents that the cell information table composes the menu screen.

A ninth aspect of the present invention is a reproducing apparatus, comprising means for determining a cell information table that composes a menu screen corresponding to the identifying information and means for reproducing the menu screen corresponding to the cell information table.

Thus, according to the present invention, it is not necessary to record a menu list and so forth in other than a file. Consequently, even if the number of selection items increases, the ratio of the menu data amount to the entire record data amount does not increase.

A tenth aspect of the present invention is a recording medium, wherein the chain information table that composes the program chain with the cell information table that composes the menu screen includes block mode information that defines a cell information group that composes the menu screens that correlate as one block.

An eleventh aspect of the present invention is a recording apparatus, comprising a means for recognizing correlation among a plurality of menu screens included in the chain information table corresponding to the block mode information in the chain information table searched by the first searching means, and a means for reproducing a second menu screen after a first menu screen is selected, when the recognizing means has determined that there is correlation between the first menu screen that is being reproduced and the second menu screen.

A twelfth aspect of the present invention is a recording medium, wherein the cell information table that composes the menu screen further includes language type information that represents a language type of characters displayed on the menu screen.

A thirteenth aspect of the present invention is a reproducing apparatus, comprising a means for determining whether or not a language type of the menu screen composed of the cell information table on the menu screen matches a language type selected by the language type selecting means corresponding to the language type information in the cell information table when the determining means has determined the cell information table that composes the menu

screen, and a means for reproducing at least one data unit searched by the third searching means as the menu screen.

Thus, according to the present invention, only a menu screen with a language type selected by the user can be reproduced from a plurality of cell information tables so as to compose a menu screen with same content but different languages.

These and other objects, features and advantages of the present invention will become more apparent in light of the following detailed description of a best mode embodiment thereof, as illustrated in the accompanying drawings.

Fig. 1 is a schematic diagram showing a data structure of an optical disc according to an embodiment of the present invention;

Fig. 2 is an example of PVD table;

Fig. 3 is an example of VTD table;

Fig. 4 is an example of L type PT table;

Fig. 5 is an example of M type PT table;

Fig. 6 is an example of DR(00) table;

Fig. 7 is an example of DR(01) table;

Fig. 8 is an example of file (n) table;

Fig. 9 is a block diagram showing a construction of an optical disc reproducing apparatus that reproduces data from the disc shown in Fig. 1;

Fig. 10 is a block diagram showing a construction of a function that determines the types of a disc and a file corresponding to a data recording format;

Fig. 11 is a block diagram showing a construction of a function that determines the number of recording sides and a reproducing side of a disc;

Fig. 12 is a schematic diagram showing a file access process of a data structure;

Fig. 13 is a flow chart showing a file access process;

Fig. 14 is a schematic diagram showing disc management information multiplexedly written to a read-in region;

Fig. 15 is a schematic diagram showing a data structure of a file;

Fig. 16 is an example of a file management table;

Fig. 17 is an example of a chain information table;

Fig. 18 is an example of a chain information table;

Fig. 19 is an example of a cell information table;

Fig. 20 is an example of a DAT;

Fig. 21 is a flow chart showing a program chain selecting process;

Fig. 22 is a schematic diagram showing an example of file relocation;

Fig. 23 is an example of tables showing branch information of three program chains;

Fig. 24 is an example of tables showing chain control information of three program chains;

Fig. 25 is a schematic diagram showing a reproducing process of three chain programs;

Fig. 26 is a table showing control information of

a program chain;

Fig. 27 is a flow chart showing a successive reproducing process of program cells;

Fig. 28 is a schematic diagram showing a real example of a successive reproducing process of program cells;

Fig. 29 is a table showing an example of control information of program chains including multiple angles;

Fig. 30 is a flow chart showing a reproduction control process of multiple angles;

Fig. 31 is a schematic diagram showing a real example of a reproducing process of multiple angles;

Fig. 32 is a schematic diagram showing a construction of chain control information in a chain information table that composes a menu screen;

Fig. 33 is a table and a schematic diagram showing a structure of a cell information table that composes a menu screen;

Fig. 34 is a schematic diagram showing a structure of a file selecting menu;

Fig. 35 is a schematic diagram showing a structure of a sequence (program chain) selecting menu;

Fig. 36 is a schematic diagram showing a structure of another menu;

Fig. 37 is a block diagram showing a structure of a function for displaying a menu;

Fig. 38 is a schematic diagram showing a file selecting process;

Fig. 39 is a table showing a cell information table group that composes a plurality of menu screens with different languages;

Fig. 40 is a schematic diagram showing multiplexedly recorded spare management information of a related art reference; and

Fig. 41 is a schematic diagram showing a menu composing process of a related art reference.

Next, with reference to the accompanying drawings, an embodiment of the present invention will be described.

Fig. 1 a schematic diagram showing a data structure of an optical disc according to an embodiment of the present invention.

The data structure of the disc is based on ISO-9660 standard. The record space of the disc is divided into a read-in region, a management region, a data region, and a read-out region. The management region includes a system area, a PVD (Primary Volume Descriptor) table, a VTD (Volume Terminate Descriptor) table, a PT (Path Table), and a DR (Directory Record). The data region is composed of a plurality of files.

As shown in Fig. 2, in the PVD table of the management region, information of the disc (volume) such as the size of the volume, the attribute of the volume, the position of the route DR, and the position of the PT is written. The content of the VTD table is defined

as shown in Fig. 3. In the PT (L type PT or M type PT), as shown in Figs. 4 and 5, hierarchical structures between DRs are written. The DR is a table group that are composed of a route DR (00) table, a route DR (01) table, and a file (n) table. In the route DR (00) table and the route DR (01) table, as shown in Figs. 6 and 7, the positions thereof are written. The file (n) table is provided for each file in the data region. As shown in Fig. 8, in the file (n) table, the position of the file and so forth are written.

As shown in Fig. 2, the PVD table is provided with an application system region. In the application system region, a disc identifier 1, a number-of-disc-sides identifier 2, a disc side identifier 3, and so forth are recorded. The disc identifier 1 represents the type of the data recording format of the disc. The number-of-disc-sides identifier 2 represents whether the disc is a double-sided disc or a single-sided disc. The disc side identifier 3 represents whether side A or side B of a double-sided disc is being reproduced. In the PVD table, the value of the BP represents the byte position from the top of the table.

As shown in Fig. 8, the file (n) table corresponding to each file is provided with an application system region. In the application system region, information (disc identifier) 4 and so forth are recorded. The disc identifier 4 represents the type of the data recording format of the file.

Fig. 9 is a schematic diagram showing a construction of an optical disc reproducing apparatus that reproduces data from a disc that has the above-described data structure. In Fig. 9, reference numeral 11 is an optical disc drive portion that drives the optical disc and reads data from the optical disc through an optical pickup. Reference numeral 12 is an MPU (Micro Processor Unit) that controls the entire system of the apparatus. Reference numeral 13 is a key input portion that supplies a user command to the MPU 12. Reference numeral 14 is an RAM portion that is used as a working region for a ROM and the MPU 12. In the ROM, a control program for the MPU 12 is stored. Reference numeral 15 is a system processor portion that demodulates and error-corrects the data that is output from the optical drive portion 11 and divides the error-corrected data into three types of data that are video (main image), audio, and sub video. Reference numeral 16 is a RAM portion that processes data. Reference numerals 17, 18, and 19 are a video decoder portion, an audio decoder portion, and a sub video decoder portion that decode the video data, the audio data, and the sub video data that are output from the system processor portion 15, respectively. Reference numeral 20 is a D/A & reproducing process portion that converts each decoded data into an analog signal, multiplexes the video data and the sub video data, and outputs the multiplexed data to an image and sound output portion 21.

Next, with reference to Figs. 10 to 13, the opera-

tion of the optical disc reproducing apparatus will be described. Fig. 10 is a block diagram showing a construction of a function that determines the types of a disc and a file corresponding to the data recording format of the disc. Fig. 11 is a schematic diagram showing a construction of a function that determines the number of recording sides of the disc and the reproducing side. Fig. 12 is a schematic diagram showing a file access process of the data structure shown in Fig. 1. Fig. 13 is a flow chart showing a file access process.

After the disc reproducing apparatus is activated or the disc is replaced, the reproducing apparatus reads the PVD table (at step 1). Thereafter, the reproducing apparatus determines whether or not the disc is based on the ISO-9660 standard corresponding to the standard identifier in the PVD table (at step 2). When the disc is based on the ISO-9660 standard, a disc recording format determining portion 31 of the reproducing apparatus checks the disc identifier 1 recorded in the application system region of the PVD table and determines whether or not the reproducing apparatus can reproduce data from the disc (applicable disc) (at step 3).

When the mounted disc is an applicable disc, a number-of-disc-recording-sides determining portion 41 of the reproducing apparatus determines the number-of-disc-sides identifier 2 recorded in the application system region (at step 4). When the mounted disc is a double-sided disc, a disc side A/B determining portion 42 of the reproducing apparatus checks the disc side identifier 3 recorded in the application system region and determines whether the reproducing side is side A or side B (at step 5).

Thereafter, the reproducing apparatus reads the PT and determines the hierarchical structure between the DRs. Next, the reproducing apparatus reads the route RD and determines the position of each file (n) table (at step 6). After that, the reproducing apparatus obtains a file name from the first file (n) table (at step 7) and determines whether or not the file name matches a predetermined file name (at step 8). When these file names do not match, the reproducing apparatus obtains the next file name (at step 9) and repeats the same operation. When these files match, a file record format determining portion 32 shown in Fig. 10 of the reproducing apparatus checks the information (disc identifier) 4 in the application system region of the file (n) table in the matched file and determines whether or not the file is applicable for the reproducing apparatus (at step 11). When the file is not applicable, the process is terminated. When the file is applicable, the reproducing apparatus checks the record position of the file corresponding to the file (n) table and accesses the file (at step 12).

Next, the multiplex recording method of the management information will be described.

On the disc, the same management information

as the information recorded in the management region is multiplexedly recorded at a plurality of positions other than the positions of the management region and the data region.

Fig. 14 shows the spare management information that is multiplexedly written at a plurality of positions in the read-in region. As shown in Fig. 14, the values that represent the positions of individual spare management information are defined by the relative distance (number of sectors) from the top addresses of the spare management regions 51 and 52.

The absolute addresses that represent the positions in a management region 53 and a data region 54 are defined by the relative distance (the number of sectors) from the top address of the management region 53. Thus, when any position of the spare management region 51 or 52 is accessed, by adding the value of a desired absolute address and an offset value of the top address of the spare management region 51 or 52, the value of the absolute address can be calculated. For example, when the top address of the first spare management region 51 is -20, the address represented by the absolute address 3 is calculated by the following expression.

$$3 + (-20) = -17$$

Likewise, when the top address of the second spare management region 52 is -10, the address represented by the absolute address 3 can be calculated by the following expression.

$$3 + (-10) = -7$$

Next, the data structure of the file recorded in the data region of the disc will be described. Fig. 15 is a schematic diagram showing the data structure of the file. As shown in Fig. 15, the file includes a file management table 5, a group of chain information tables 6, a group of cell information tables 7, a group of DUT allocation tables (referred to as DATs) 8, and a group of DUTs (data units) 9.

As shown in Fig. 16, the file management table 5 includes the number of chain information tables, the number of cell information tables, the number of DUTs (data units), the number of sectors, and pointers that represent the top of each table.

As shown in Figs. 17 and 18, in the chain information table 6, information that composes a program chain is written. A program chain is a unit that composes one story. Each program chain is composed by linking a plurality of programs in the order of the reproduction. A program is composed of a group of at least one unit called a program cell. In other words, the chain information table 6 includes information that composes one program chain in which a plurality of cell information tables 7 are selectively linked. In the file, a plurality of chain information tables 6 are successively placed in the order of chain numbers.

As shown in Fig. 19, in the cell information table 7, information that composes program cells is written. A program cell is a part that composes one program.

Each program cell is composed by linking a plurality of DUTs in the order of reproduction. In other words, the cell information table 7 includes information that composes one program cell in which a plurality of DUTs 9 are selectively linked. In the file, a plurality of cell information tables 7 are successively linked in the order of cell numbers.

As shown in Fig. 20, in the DAT 8, information that represents the position of the DUT is written as the relative distance (number of sectors) from the top of the file. In the file, a plurality of DATs 8 are successively placed in the order of the DUT numbers.

The DUT 9 is composed of a plurality of types of data that are video data, audio data, sub video data that are synchronously reproduced. The reproducing time of each DUT 9 is not defined. In the file, the DUTs 9 are placed in the order of the DUT numbers.

Next, with reference to Fig. 21, a process for selecting a program chain will be described.

The reproducing apparatus can reproduce any program chain selected by the user from a plurality of program chains that are present in a file.

The reproducing apparatus obtains a required file and then reads the file management table 5 from the file (at step 1). Thereafter, the reproducing apparatus obtains the number of program chains in the file, the number of program cells in the file, the number of DUTs in the file, the number of sectors in the file, and the pointers that represent the top of each table (at step 3). Next, the reproducing apparatus obtains the content of the first chain information table corresponding to the obtained pointers (at step 4) and resets the counter value that represents the chain number to "0" (at step 5).

After that, the reproducing apparatus determines whether or not the chain number represented by the counter matches a chain number designated by the user (at step 6). When these number do not match, with a pointer that is obtained by adding the length of the table written to the chain information table to the top pointer, the reproducing apparatus obtains the content of the next chain information table (at step 7). Thereafter, the reproducing apparatus increments the chain number by "1" (at step 8) and determines whether or not the chain number of the counter matches the chain number designated by the user. The reproducing apparatus repeats steps 6 to 8 until the chain number represented by the counter matches the chain number designated by the user.

When the chain number represented by the counter matches the chain number designated by the user, the reproducing apparatus obtains the number of program cells that compose the program chain, the number of DUTs, the number of sub video channels, the number of audio streams, and so forth from the chain information table (at step 9). Thereafter, the reproducing apparatus obtains the number of branch points (NBP) in the chain information table and the top poin-

ter of the chain control information (SCINFO) from the obtained information (at step 10). After that, the reproducing apparatus obtains the top chain control information (SCINFO) from the obtained top pointer (at step 11) and starts the reproduction control of the program chain corresponding to the chain control information (SCINFO) (at step 12).

The top positions of the file management table 5, the chain information table 6, the cell information table 6, the cell information table 7, the DAT 8, and the DUT 9 in the file shown in Fig. 15 are defined by the relative distance (the number of sectors) from the top of the file. In the following description, the number of sectors of the file management table 5 is represented by a. The number of sectors of all chain information tables 6 is represented by b. The number of sectors of all cell information tables is represented by c. The number of sectors of all DATs is represented by d. Thus, the top position of the file management table is represented by 0. The position of the top chain information table is represented by a. The position of the top cell information table is represented by a+b. The position of the top DAT is represented by a+b+c. The position of the top DUT is represented by a+b+c+d.

Since the position in the file is represented by the relative distance (the number of sectors) from the top of the file, as shown in Fig. 22, when the file is relocated to another position of the data region, it is not necessary to change the value that represents the position.

In the file structure of this optical disc, a plurality of program chains can share the same program cells.

As shown in Fig. 18, in the chain information table, the number of branch points (NBP) that represents the number of program cells shared with another program chain and branch information (BINFO) that is the program cell number are written. Figs. 23 and 24 show examples of the branch information (BINFO) and chain control information (SCINFO) in the case that program chains A, B, and C share program cells. In the chain control information (SCINFO), program cell numbers are written in the order of reproduction thereof. The reproducing apparatus successively selects and reproduces program cells corresponding to the chain control information (SCINFO). Thus, the program chains A, B, and C are reproduced corresponding to the process shown in Fig. 25. In Fig. 25, (0) to (8) represent program cell numbers and reproducing regions thereof.

Next, the operation in the case that a program chain is switched while one of program chains A, B, and C is being reproduced will be described.

1) When the program chain A is switched to the program chain B while the program cell 1 of the program chain A is being reproduced, the program chain B is reproduced from the first program cell 5.

2) When the program chain A is switched to the

program chain C while the program cell 1 of the program chain A is being reproduced, the program chain C is reproduced from the first program cell 7.

3) When the program chain A is switched to the program chain B after the program cell 1 of the program chain A has been reproduced, the program chain B is reproduced from the next program cell 2. This is because the program chain B has the program cell 1 that is shared with the program chain A. To prevent the same program cell from being redundantly reproduced, the program chain B is reproduced from the next program cell 2.

4) When the program chain A is switched to the program chain C after the program cell 1 of the program chain A has been reproduced, the program chain C is reproduced from the first program cell 7.

5) When the program chain A is switched to the program chain B after the program cell 2 of the program chain A has been reproduced, the program chain B is reproduced from the program cell 6. The reason is the same as 3) above.

6) When the program chain A is switched to the program chain C after the program cell 2 of the program chain A has been reproduced, the program chain C is reproduced from the first program cell 7.

7) When the program chain A is switched to the program chain B after the program cell 3 of the program chain A has been reproduced, the program chain B is reproduced from the program cell 6.

8) When the program chain A is switched to the program chain C after the program cell 3 of the program chain A has been reproduced, the program chain C is reproduced from the program cell 8. This is because the program chain C has the program cell 3 that is shared with the program chain A. To prevent the same program cell from being redundantly reproduced, the program chain C is reproduced from the program cell 8.

When a first program chain is switched to a second program chain that shares program cells with the first program chain, after the shared program cells have been reproduced, the next program chain is reproduced.

Next, a process for controlling the reproduction of a program chain will be described.

As shown in Fig. 18, in the chain information table, the chain control information (SCINFO) is successively recorded in the order of the reproduction of the program cells. Thus, by reading the chain control information, the program cells can be successively reproduced (namely, the program chain can be reproduced).

As shown in Figs. 18 and 26, the chain control in-

formation (SCINFO) includes a two-bit reproduction control area 61. The reproducing apparatus can recognize the content of the control of program cells that are successively reproduced corresponding to the reproduction control information.

The content of the reproduction control information is:

00 : Successively reproduces the next program cell without waiting time after a program cell is reproduced (presence of continuity of programs).

01 : Successively reproduces the next program cell without waiting time after a program cell is reproduced (absence of continuity of programs).

10 : Reproduces a program cell with waiting time (PWAIT) designated by cell information table after another program cell is reproduced.

11 : Stops the reproducing operation, after a program cell is reproduced.

Next, a real example of the successive reproduction control of program cells corresponding to the reproduction control information will be described.

Fig. 26 shows an example of the chain control information (SCINFO). In this example, a program chain is composed of five program cells. The angle modes of the program cells are "00". A multi-angle reproduction is not designated. In the multi-angle reproduction, the user can select one of program cells that can be reproduced in the same time on the same time axis. For example, in the case of a baseball program on TV, the user can select one of the two images which have been photographed and received by cameras on the first base side and the second base side.

Next, with reference to a flow chart of Fig. 27, a process for controlling successive reproduction of program cells will be described.

The reproducing apparatus obtains the first control information (SCINFO) from the chain information table (at step 1) and reads the first program cell number therefrom (at step 2). Thereafter, the reproducing apparatus reads the top pointer of the cell information table from the file management table and obtains a desired cell information table corresponding to the top pointer and the program cell number (at step 3). Next, the reproducing apparatus reproduces program cells corresponding to the content of the obtained cell information table (at step 4).

At this point, the reproducing apparatus reads the information of the reproduction control area of the chain control information and controls the successive reproduction of the program cells corresponding to the reproduction control information.

When the reproduction control information is "00" (at step 5), after the reproducing apparatus has reproduced the program cell, it obtains the next chain control information (SCINFO) (at step 11) and then starts reproducing the next program cell.

When the reproduction control information is "01" (at step 6), the reproducing apparatus executes a

broken link process such as mute just before it completes reproducing the program cell (at step 9). After the reproducing apparatus has reproduced the program cell, it obtains the next program chain control information (SCINFO) and then starts reproducing the next program cell.

When the reproduction control information is "10" (at step 7), after the reproducing apparatus has reproduced the program cell, it performs a wait process for time (PWAIT) designated by the cell information table (at step 10). After the wait time elapsed, the reproducing apparatus obtains the next chain control information (SCINFO) and starts reproducing the next program cell.

When the reproduction control information is "11", after the reproducing apparatus has reproduced the program cell, it stops reproducing the program chain (at step 8).

The real process of the reproduction control for the chain control information shown in Fig. 26 will be described as follows. Fig. 28 shows the process of the reproduction control.

Chain control information number 0 : S1 -> S2 (obtained cell number 0) -> S3 -> S4 (reproduced cell number) -> S5 -> S11

Chain control information number 1 : -> S2 (obtained cell number 1) -> S3 -> S4 (reproduced cell number 1) -> S5 -> S6 -> S9 -> S11

Chain control information number 2 : -> S2 (obtained cell number 4) -> S3 -> S4 (reproduced cell number 4) -> S5 -> S11

Chain control information number 3 : -> S2 (obtained cell number 2) -> S3 -> S4 (reproduced cell number 2) -> S5 -> S6 -> S7 -> S10 (wait process) -> S11

Chain control information number 4 : -> S2 (obtained cell number 3) -> S3 -> S4 (reproduced cell number 3) -> S5 -> S6 -> S7 -> S8 -> end

Next, a process for multi-angle reproduction of program cells will be described.

As shown in Figs. 29 and 18, in the chain control information of the chain information table, 2-bit angle mode information 71 and 4-bit angle number 42 are recorded. The content of the angle mode information 71 is as follows. The angle block is a group of some program cells that are selectively reproduced in the same time on the same time axis.

00 : No angle block

10 : Start/continuance of angle block

11 : End of angle block.

Angle numbers 72 are successively assigned to program cells that compose an angle block. When the user selects an angle number, the program cell corresponding to the angle number is reproduced.

Next, the process for the multi-angle reproduction will be described. Fig. 30 is a flow chart showing the process for the multi-angle reproduction control.

The reproducing apparatus obtains the first chain control information (SCINFO) from the chain informa-

tion table and reads the first program cell number therefrom (at step 2). Thereafter, the reproducing apparatus reads the top pointer of the cell information table from the file management table and obtains a desired cell information table corresponding to the top pointer and the program cell number (at step 3). The reproducing apparatus reads the angle mode information 71 of the first chain control information and executes the multi-angle reproduction control corresponding to the information in the following manner.

When the angle mode information is "10" (start/continuance of angle block) (at step 6), the reproducing apparatus determines whether or not the user has designated an angle number (at step 7). When an angle number has not been designated, the reproducing apparatus selects a default angle number (0) (at step 8) and sets the angle mode flag (at step 9). When an angle number has been designated, the reproducing apparatus just sets the angle mode flag (at step 9).

Thereafter, the reproducing apparatus determines whether or not the present program cell is a program cell with an angle number designated by the user (at step 10). When the determined result is YES, the reproducing apparatus obtains a corresponding cell information table and executes the reproduction of the program cell corresponding to the content of the cell information table (at step 11). Thereafter, the reproducing apparatus resets the angle mode flag (at step 12). When the determined result is "NO", the reproducing apparatus does not reproduce the present program cell. Thus, the reproducing apparatus keeps the angle mode flag in the set state.

Next, the reproducing apparatus reads the information of the reproduction control area 61. When the information is not "11" (stops reproducing the program chain) (at step 13), the reproducing apparatus obtains the next chain control information from the chain information table (at step 15) and repeats the same process at step 2.

When the angle mode information 71 at step 4 is "11" (end of the angle block), the reproducing apparatus determines whether or not the angle mode flag has been set (at step 16). When the angle mode flag has been reset, the reproducing apparatus obtains the next chain control information through step 13 (at step 15). Alternatively, the reproducing apparatus terminates the process for reproducing the program chain (at step 14).

Thus, the multi-angle reproduction control is executed corresponding to the chain control information shown in Fig. 29 as follows. Fig. 31 shows the process for the multi-angle reproduction control. In the following description, it is assumed that the angle number designated by the user is "1".

Chain control information number 0 : S1 -> S2 (obtained cell number 0) -> S3 -> S4 -> S5 -> S11 (reproduced cell number 0) -> S12 -> S13 -> S15

Chain control information number 1 : -> S2 (obtained cell number 1) -> S3 -> S4 -> S5 -> S6 -> S7 -> S9 -> S10 -> S13 -> S15

Chain control information number 2 : -> S2 (obtained cell number 5) -> S3 -> S4 -> S5 -> S6 -> S7 -> S9 -> S10 -> S11 (reproduced cell number 5) -> S12 -> S13 -> S15

Chain control information number 3 : -> S2 (obtained cell number 6) -> S3 -> S4 -> S16 -> S13 -> S15

Chain control information number 4 : -> S2 (obtained cell number 2) -> S3 -> S4 -> S5 -> S11 (reproduced cell number 2) -> S12 -> S13 -> S15

Chain control information number 5 : -> S2 (obtained cell number 3) -> S3 -> S4 -> S5 -> S6 -> S7 -> S8 -> S9 -> S10 -> S11 (reproduced cell number 3) -> S12 -> S13 -> S15

Chain control information number 6 : -> S2 (obtained cell number 7) -> S3 -> S4 -> S16 -> S13 -> S15

Chain control information number 7 : -> S2 (obtained cell number 4) -> S3 -> S4 -> S5 -> S6 -> S11 (reproduced cell number 4) -> S12 -> S13 -> S14 -> end

Next, specific code added corresponding to an application type of a program chain of this disc will be described.

As shown in Fig. 17, in the chain information table, 4-bit type information 74 and 8-bit specific code 73 are recorded. The 4-bit type information 74 represents an application type of a program chain. The 8-bit specific code 73 represents detail description of the application type. The specific code 73 represents detailed content, and the detailed content corresponding to the code is defined uniquely to each of the application type. For example, as an application of a program chain, an orchestral music program and an instrument are considered. In the case of an orchestral music program, the specific code represents the language type of the superimposed text. In the case of the instrument, the specific code represents the type of the instrument. Thus, without need to extend the specific code, with the specific code having a fixed length, detailed contents of many types can be defined.

Next, a process for displaying a menu of the disc will be described.

Fig. 32 is a schematic diagram showing the structure of chain control information (SCINFO) in the chain information table that composes a menu screen. Fig. 33 is a table and a schematic diagram showing the structure of a cell information table composing a menu screen.

As shown in Fig. 32, the chain control information (SCINFO) of the chain information table includes 2-bit block mode information 81 and 4-bit block type 82 that represents the type of a block. The block mode information 81 represents the correlation among a plurality of program cells. In other words, when the block mode information 81 is "00", the program cell is

not a cell that composes the block. When the block mode information 81 is "01", the program cell is a cell at the top of the block. When the block mode information 81 is "10", the program cell is a cell except the top cell and the end cell in the block. When the block mode information 81 is "11", this program cell is a cell at the end of the block. When the block type 82 is "0000", this program cell is not a block. When the block type 82 is "0001", this program cell is an angle block. When the block type 82 is "0010", this program cell is a menu block.

As shown in Fig. 33, in the cell information table, type information 83 and specific code 84 are written. The type information represents the type of a program cell. As the types of program cells, there are movie, orchestra, and various menus. As menu types, there are file selecting menu, sequence (program chain) selecting menu, audio stream selecting menu, sub video channel selecting menu, program selecting menu, angle selecting menu, and so forth. When the type of the program cell is the menu, the specific code 84 represents the language type.

Fig. 34 is a schematic diagram showing a structure of a file selecting menu. As shown in Fig. 34, the file selecting menu is composed with the top file in the data region. In other words, this file is composed of at least one chain information table S0 including at least one cell information table C0. In Fig. 34, P0 represents a program composing a program chain. A program is composed of at least one cell information table.

Fig. 35 is a schematic diagram showing a structure of a sequence (program chain) selecting menu. As shown in Fig. 35, this menu is composed of chain information tables S0 at the top portions of individual files. In the chain information table, cell information tables C120 and C200 that compose the audio stream selecting menu and the sub video channel selecting menu can be added. In this case, a plurality of cell information tables that composes individual menus are correlated by the block mode information 81 in the chain information table. When one menu is composed of a plurality of screens (a plurality of cell information tables), each cell information is correlated by the block mode information 81.

One chain information table can compose a menu and non-menu data by using the block mode information 81 and the block type 82. Fig. 36 is a schematic diagram in this case. In this example, the chain information table S1 includes two cell information tables C20 and C21 that compose the angle selecting menu and the program selecting menu. The cell information tables C20 and C21 are placed only at the top portion of the chain information table S1. The next chain information table S2 includes one cell information table C22 that composes a low order program selecting menu of the program selecting menu. The cell information table C22 is placed only at the top portion of

the chain information table S2. The chain information table S3 includes one cell information table C23 that composes a low order angle selecting menu of the angle selecting menu. The cell information table C23 is placed at the top portion of the chain information table S3.

Next, a reproducing apparatus that accomplishes the menu display of the disc will be described.

Fig. 37 is a block diagram showing the construction of the function that accomplishes the menu display. In Fig. 37, reference numeral 91 is a key input portion that designates a selection item on the menu screen and a language type. Reference numeral 92 is a menu determining/selecting portion that determines a cell information table that composes a menu screen corresponding to the type information 83 recorded in the cell information table and recognizes an item number selected on the menu screen. Reference numeral 93 is a reproduction control information storing portion that stores reproduction control information recorded in a chain information table including the cell information table that composes the menu screen. Reference numeral 94 is a cell reproduced data storing portion that stores at least one data unit as cell reproduced data corresponding to the cell information table that composes the menu screen. Reference numeral 95 is a cell reproduction control portion that controls the reproduction of cell reproduced data stored in the cell reproduced data storing portion 94. Reference numeral 96 is a display portion that displays the menu screen. Reference numeral 97 is a menu block determining portion that recognizes the correlation among a plurality of cell information tables that composes the menu screen corresponding to the block mode information 81 in the chain information table. Reference numeral 98 is a menu block switching portion that switches the present menu screen to the next menu screen after an item has been selected on the menu screen that is being reproduced when the menu block determining portion 97 has recognized the correlation between the present menu screen and the next reproducing menu screen. Reference numeral 99 is a specific code determining/storing portion that stores the specific code 73 of the cell information table that composes the menu screen and determines whether or not the language type of the menu screen matches the predetermined language type.

Next, the operation of the menu display of the disc will be described. Fig. 38 is a schematic diagram showing a process for selecting a file.

The reproducing apparatus obtains the chain information table at the top of the top file (file 0) in the data region and stores the obtained reproduction control information of the chain information table in the reproduction control information storing portion 93. Next, the reproducing apparatus obtains the first cell information table corresponding to the top chain control information. The menu determining/selecting por-

tion 92 reads the program cell type information 83 included in the cell information table and determines whether or not the program cell type is a menu. When the program cell type is a menu, the cell reproduction control portion 95 reproduces the program cell. The display portion 96 displays a file selecting menu screen 101 as shown in Fig. 38. The menu screen 101 displays each file number along with the corresponding file name (work name). When the user selects any file number with the key input portion 91, the menu determining/selecting portion 92 recognizes the selected file number and obtains the top chain information table in the file corresponding to the file number. The reproduction control information storing portion 93 stores the reproduction control information of the chain information table. Thereafter, the reproducing apparatus obtains the first cell information table corresponding to the top chain control information. After that, the menu determining/ selecting portion 92 reads the program cell type information 83 included in the cell information table. When the program cell type is a menu, the cell reproduction control portion 95 reproduces the program cell and displays the next menu screen on the display portion 96.

The menu block determining portion 97 reads the block mode information 81 and the block type 82 from the chain information table and determines whether or not each cell information in the chain information table has correlation as a menu block. When the present menu screen and the next menu screen correlate, the menu block switching portion 98 switches the present menu screen to the next menu screen after an item of the present menu screen has been selected. In such a manner, all the menus can be successively displayed up to the last cell of the menu block.

In addition, on the disc, a plurality of menu screens with the same content but different languages are recorded as one menu block. The language type of the menu is represented by the specific code 84 in the cell information table. Fig. 39 is a schematic diagram showing an example of a cell information table group that composes a plurality of menu screens with different languages. In this case, when the user designates a language type, the specific code determining/storing portion 99 selects only a program cell that composes the menu corresponding to the language type from the menu group that composes one menu block and successively reproduces it.

Although the present invention has been shown and described with respect to a best mode embodiment thereof, it should be understood by those skilled in the art that the foregoing and various other changes, omissions, and additions in the form and detail thereof may be made therein without departing from the spirit and scope of the present invention.

Claims

1. A recording medium, comprising:
 - a data region in which data is recorded as a file corresponding to a predetermined data recording format; and
 - a management region including medium identifying information that represents the type of the data recording format and file identifying information that represents the type of the data recording format of the file.
2. A recording medium having two opposite sides, either or both of which are selective as recording sides, comprising:
 - a data region in which data is recorded; and
 - a management region including number-of-recording-sides identifying information that represents the number of recording sides of the recording medium and recording side identifying information that represents the recording side.
3. A recording medium, comprising:
 - a data region in which data is recorded;
 - a management region in which management information is recorded, the management information being adapted for managing data recorded in said data region; and
 - a plurality of spare management regions in which management information with the same content as the management region is recorded, values representing the positions in the spare management regions being represented with relative distance from the top addresses thereof.
4. The recording medium as set forth in claim 1, further comprising a plurality of spare management regions in which management information with the same content as the management region is recorded, values representing the positions in the spare management regions being represented with relative distance from the top addresses thereof.
5. The recording medium as set forth in claim 2, further comprising a plurality of spare management regions in which management information with the same content as the management region is recorded, values representing the positions in the spare management regions being represented with relative distance from the top addresses thereof.
6. A recording medium on which data is recorded as a file, the file comprising:
 - a first region in which a group of a data unit that is a group of a plurality of types of data that

are synchronously reproduced;

a second region in which at least one cell information table that is a program cell composed by selectively linking at least one data unit recorded in said first region; and

a third region in which at least one chain information table that is a program chain composed by selectively linking at least one cell information table recorded in said second region.

7. The recording medium as set forth in claim 6, wherein the positions of the data unit, the cell information table, and the chain information table are defined with relative distances from the top address of the file thereof.

8. The recording medium as set forth in claim 6, the chain information table comprising:

a cell number sequence that represents a plurality of program cell numbers composing the program chain and the order of reproduction of the program cell; and

reproduction control information that defines reproduction method of the program chain for each program cell.

9. The recording medium as set forth in claim 8, wherein the types of the reproduction control information includes at least:

first reproduction control information that represents the reproduction of a second program cell after a first program cell to be controlled is reproduced;

second reproduction control information that represents the reproduction of a second program cell with waiting time after a first program cell to be controlled is reproduced; and

third reproduction control information that represents the stop of the reproduction after a program cell to be controlled is reproduced.

10. The recording medium as set forth in claim 6, wherein the chain information table further includes:

a cell number sequence that represents a plurality of program cell numbers composing the program chain and the order of reproduction of the program cell; and

mode information that represents whether or not each program cell represented by the cell number sequence is a program cell that can be selectively reproduced along with another program cell in the same time on the same time axis.

11. The recording medium as set forth in claim 6, wherein the chain information table further includes:

type information that represents an appli-

cation type of the program chain; and

a specific code that represents detailed content of said type information and a specific code that represents detailed content of said information, the detailed content corresponding to the code being defined uniquely to each of the application type.

12. The recording medium as set forth in claim 6,

wherein the file includes at least one cell information table that composes a menu screen on which any data item to be displayed is selected; and

wherein the cell information table that composes the menu screen includes identifying information that represents that the cell information table composes the menu screen.

13. The recording medium as set forth in claim 12, wherein the chain information table that composes the program chain with the cell information table that composes the menu screen includes block mode information that defines a cell information group that composes the menu screens that correlate as one block.

14. The recording medium as set forth in claim 12, wherein the cell information table that composes the menu screen further includes language type information that represents a language type of characters displayed on the menu screen.

15. A reproducing apparatus for reproducing a recording medium having a data region in which data is recorded as a file corresponding to a predetermined data recording format, and a management region including medium identifying information that represents the type of the data recording format and file identifying information that represents the type of the data recording format of the file, comprising:

first determining means for reading medium identifying information recorded in the management region and determining a type based on a data recording format of the recording medium corresponding to the medium identifying information; and

second determining means for reading the file identifying information of each file recorded in the management region and determining a type based on the data recording format of each file recorded on the recording medium corresponding to the file identifying information.

16. A reproducing apparatus for reproducing a recording medium having two opposite sides, either or both of which are selective as recording sides, including a data region in which data is recorded,

and a management region including number-of-recording-sides identifying information that represents the number of recording sides of the recording medium and recording-side identifying information that represents the recording side, comprising:

number-of-recording-sides determining means for reading the number-of-recording-sides identifying information recorded in the management region and determining the number of recording sides of the recording medium; and
recording-side determining means for reading the recording-side identifying information recorded in the management region and determining the recording side of the recording medium to be reproduced.

17. A reproducing apparatus for reproducing a recording medium on which data is recorded as a file, the file including a first region in which a group of a data unit that is a group of a plurality of types of data that are synchronously reproduced, a second region in which at least one cell information table that is a program cell composed by selectively linking at least one data unit recorded in said first region, and a third region in which at least one chain information that is a program chain composed by selectively linking at least one cell information table recorded in said second region, comprising:

first searching means for searching any chain information table recorded in the third region;

second searching means for searching at least one cell information table that composes the program chain from the second region corresponding to the searched chain information table; and

third searching means for searching at least one data unit that composes the program cell from the first region corresponding to the cell information table searched by said second searching means.

18. A reproducing apparatus for reproducing a recording medium on which data is recorded as a file, the file including a first region in which a group of a data unit that is a group of a plurality of types of data that are synchronously reproduced, a second region in which at least one cell information table that is a program cell composed by selectively linking at least one data unit recorded in said first region, and a third region in which at least one chain information that is a program chain composed by selectively linking at least one cell information table recorded in said second region, the file including at least one cell information table that composes a menu screen on which

any data item to be displayed is selected, the cell information table that composes the menu screen including identifying information that represents that the cell information table composes the menu screen, comprising:

first searching means for searching any chain information table recorded in the third region;

second searching means for searching at least one cell information table that composes the program chain from the second region corresponding to the searched chain information table;

determining means for determining whether or not the cell information table is a cell information table that composes the menu screen corresponding to the identifying information of the cell information table searched by said second searching means;

third searching means for searching at least one data unit that composes the program cell from the first region corresponding to the cell information cell when said determining means has determined the cell information table that composes the menu screen; and

menu reproducing means for reproducing at least one data unit searched by said third searching means as the menu screen.

19. A reproducing apparatus for reproducing a recording medium on which data is recorded as a file, the file including a first region in which a group of a data unit that is a group of a plurality of types of data that are synchronously reproduced, a second region in which at least one cell information table that is a program cell composed by selectively linking at least one data unit recorded in said first region, and a third region in which at least one chain information that is a program chain composed by selectively linking at least one cell information table recorded in said second region, the file including at least one cell information table that composes a menu screen on which any data item to be displayed is selected, the cell information table that composes the menu screen includes identifying information that represents that the cell information table composes the menu screen, the chain information table that composes the program chain with the cell information table that composes the menu screen including block mode information that defines a cell information group that composes the menu screens that correlate as one block, comprising:

first searching means for searching any chain information table recorded in the third region;

second searching means for searching at least one cell information table that composes the program chain from the second region corresponding to the searched chain information table;

sponding to the searched chain information table;

determining means for determining whether or not the cell information table is a cell information table that composes the menu screen corresponding to the identifying information of the cell information table searched by said second searching means;

third searching means for searching at least one data unit that composes the program cell from the first region corresponding to the cell information cell when said determining means has determined the cell information table that composes the menu screen;

menu reproducing means for reproducing at least one data unit searched by said third searching means as the menu screen;

recognizing means for recognizing correlation among a plurality of menu screens included in the chain information table corresponding to the block mode information in the chain information table searched by said first searching means; and

menu screen switching means for reproducing a second menu screen after a first menu screen is selected, when said recognizing means has determined that there is correlation between the first menu screen that is being reproduced and the second menu screen.

20. A reproducing apparatus for reproducing a recording medium on which data is recorded as a file, the file including a first region in which a group of a data unit that is a group of a plurality of types of data that are synchronously reproduced, a second region in which at least one cell information table that is a program cell composed by selectively linking at least one data unit recorded in said first region, and a third region in which at least one chain information that is a program chain composed by selectively linking at least one cell information table recorded in said second region, the file including at least one cell information table that composes a menu screen on which any data item to be displayed is selected, the cell information table that composes the menu screen including identifying information that represents that the cell information table composes the menu screen, the cell information table that composes the menu screen further including language type information that represents a language type of characters displayed on the menu screen, comprising:

first searching means for searching any chain information table recorded in the third region;

second searching means for searching at least one cell information table that composes the program chain from the second region corre-

sponding to the searched chain information table;

first determining means for determining whether or not the cell information table is a cell information table that composes the menu screen corresponding to the identifying information of the cell information table searched by said second searching means;

language type selecting means for pre-selecting a language type of the menu screen;


second determining means for determining whether or not a language type of the menu screen composed of the cell information table on the menu screen matches a language type selected by said language type selecting means corresponding to the language type information in the cell information table when said determining means has determined the cell information table that composes the menu screen;

third searching means for searching at least one data unit that composes the program cell corresponding to the cell information table when said second determining means has determined that the language types match; and

menu reproducing means for reproducing at least one data unit searched by said third searching means as the menu screen.

FIG. 1

PHYSICAL SECTOR SIZE : 1024 BYTES
 LOGICAL SECTOR SIZE : 2048 BYTES
 LOGICAL BLOCK SIZE : 1024 BYTES



DISC STRUCTURE

FIG. 2

BP	COLUMN NAME	DATA TYPE
1	TYPE OF VOLUME DESCRIPTOR	NUMERIC, (01H)
2~6	STANDARD DESCRIPTOR	CD001
7	REVISION NUMBER OF VOLUME DESCRIPTOR	NUMERIC, (01H)
8	NOT USED	(00H). BYTE
9~40	SYSTEM IDENTIFIER	CHARACTER
41~72	VOLUME IDENTIFIER	CHARACTER
73~80	NOT USED	(00H). BYTE
81~88	SIZE OF VOLUME SPACE	NUMERIC
89~120	NOT USED	NUMERIC
121~124	SIZE OF VOLUME GROUP	NUMERIC
125~128	VOLUME SEQUENCE NUMBER	NUMERIC
129~132	LENGTH OF LOGICAL BLOCK	NUMERIC
133~140	SIZE OF PATH TABLE	NUMERIC
141~144	POSITION OF L TYPE PATH TABLE	NUMERIC
145~148	POSITION OF ANY L TYPE PATH TABLE	NUMERIC
149~152	POSITION OF M TYPE PATH TABLE	34 BYTES
153~156	POSITION OF ANY M TYPE PATH TABLE	CHARACTER
157~190	DIRECTORY RECORD FOR ROUTE DIRECTORY	34 BYTES
191~318	VOLUME GROUP IDENTIFIER	CHARACTER
319~446	IDENTIFIER OF PUBLISHER	CHARACTER
447~574	IDENTIFIER OF DATA EDITOR	CHARACTER
575~702	IDENTIFIER OF APPLICATION SYSTEM	CHARACTER
703~739	IDENTIFIER OF COPYRIGHT FILE	CHARACTER
740~776	IDENTIFIER OF ABSTRACT FILE	CHARACTER
777~813	IDENTIFIER OF BIBLIOGRAPHY FILE	CHARACTER
814~830	DATE AND TIME OF VOLUME CREATION	NUMERIC, NUMERIC VALUE
831~847	DATE AND TIME OF VOLUME UPDATE	NUMERIC, NUMERIC VALUE
848~864	DATE AND TIME OF VOLUME EXPIRATION	NUMERIC, NUMERIC VALUE
865~881	DATE AND TIME OF VOLUME ISSUANCE	NUMERIC, NUMERIC VALUE
882	REVISION NUMBER OF FILE STRUCTURE	NUMERIC
883	(FOR FUTURE STANDARDIZATION)	(00H). BYTE
884~1395	FOR APPLICATION SYSTEM	NOT DEFINED
884~1024	(NOT USED)	
1025~1042	《SYSTEM IDENTIFIER》	
1025~1030	SYSTEM IDENTIFIER	
1031~1032	1 — SYSTEM IDENTIFIER + REVISION NUMBER	CHARACTER, NUMERIC, NUMERIC VALUE, ETC. (01H, 00H)
1033~1036	RESERVED	
1037	2 — NUMBER OF DISC SIDES IDENTIFIER	IDENTIFICATION OF SINGLE SIDED (00H)/DOUBLE SIDED (01H)
1038	3 — DISC SIDE IDENTIFIER	IDENTIFICATION OF SIDE A (00H)/SIDE B (01H)
1039~1042	DEFAULT TITLE	DEFAULT REPRODUCTION FILE NUMBER
1396~2048	(FOR FUTURE STANDARDIZATION)	(00H) BYTE

PVD TABLE

FIG. 3

BP	COLUMN NAME	DETA TYPE
1	TYPE OF VOLUME DESCRIPTOR	NUMERIC VALUE. (FFH)
2~6	STANDARD IDENTIFIER	CD001
7	REVISION NUMBER OF VOLUME DESCRIPTOR	NUMERIC VALUE. (01H)
8~2048	(FOR FUTURE STANDARDIZATION)	(00H) BYTE

VTD TABLE

FIG. 4

BP	COLUMN NAME	DETA TYPE
1	LENGTH OF DIRECTORY IDENTIFIER	(01H)
2	LENGTH OF EXTENDED ATTRIBUTE RECORD	(00H)
3~6	POSITION OF EXTENT	NUMERIC VALUE (POSITION OF L TYPE PATH TABLE (01H,00H)
7~8	PARENT DIRECTORY NUMBER	
9~10	DIRECTORY IDENTIFIER	(00H,00H)

L TYPE PT TABLE

18

FIG. 5

BP	COLUMN NAME	DETA TYPE
1	LENGTH OF DIRECTORY IDENTIFIER	(01H)
2	LENGTH OF EXTENDED ATTRIBUTE RECORD	(00H)
3~6	POSITION OF EXTENT	NUMERIC VALUE (POSITION OF M TYPE PATH TABLE (01H,00H)
7~8	PARENT DIRECTORY NUMBER	
9~10	DIRECTORY IDENTIFIER	(00H,00H)

M TYPE PT TABLE

FIG. 6

BP	COLUMN NAME	DATA TYPE
1	LENGTH OF DIRECTORY RECORD	(22H)
2	LENGTH OF EXTENDED ATTRIBUTE RECORD	(00H)
3~10	POSITION OF EXTENT	(POSITION OF DIRECTORY RECORD ITSELF)
11~18	DATA LENGTH	NUMERIC VALUE
19~25	DATE AND TIME OF RECORD	NUMERIC VALUE
26	FILE FLAG	(02H)
27	SIZE OF FILE UNIT	(00H)
28	SIZE OF INTERLEAVE INTERVALS	(00H)
29~32	VOLUME SEQUENCE NUMBER	NUMERIC VALUE
33	LENGTH OF FILE IDENTIFIER	(01H)
34	FILE IDENTIFIER	(00H)

DR (00) TABLE

FIG. 7

BP	COLUMN NAME	DATA TYPE
1	LENGTH OF DIRECTORY RECORD	(22H)
2	LENGTH OF EXTENDED ATTRIBUTE RECORD	(00H)
3~10	POSITION OF EXTENT	NUMERIC VALUE (POSITION OF DIRECTORY RECORD)
11~18	DATA LENGTH	NUMERIC VALUE
19~25	DATE AND TIME OF RECORD	NUMERIC VALUE
26	FILE FLAG	(02H)
27	SIZE OF FILE UNIT	(00H)
28	SIZE OF INTERLEAVE INTERVALS	(00H)
29~32	VOLUME SEQUENCE NUMBER	NUMERIC VALUE
33	LENGTH OF FILE IDENTIFIER	(01H)
34	FILE IDENTIFIER	(01H)

DR (01) TABLE

FIG. 8

BP	COLUMN NAME	DETA TYPE
1	LENGTH OF DIRECTORY RECORD	(3CH)
2	LENGTH OF EXTENDED ATTRIBUTE LENGTH	(00H)
3~10	POSITION OF EXTENT	NUMERIC VALUE (REAL STORAGE POSITION OF FILE)
11~18	DATA LENGTH	NUMERIC VALUE
19~25	DATE AND TIME OF RECORD	NUMERIC VALUE
26	FILE FLAG	(00H)
27	SIZE OF FILE UNIT	(00H)
28	SIZE OF INTERLEAVE INTERVALS	(00H)
29~32	VOLUME SEQUENCE NUMBER	NUMERIC VALUE
33	LENGTH OF FILE IDENTIFIER	(0EH)
34~47	FILE IDENTIFIER	CHARACTER, NUMERIC (FILE NAME)
48	NOT USED	(00H)
49~60	SYSTEM USE	
49~54	SYSTEM IDENTIFIER	
55~56	4. ~ DISC IDENTIFIER + REVISION NUMBER	
57~60	RESERVED	CHARACTER, NUMERIC, NUMERIC VALUE, ETC. (01H, 00H)

FILE (n) TABLE

FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

PARAMETER	DESCRIPTION	NUMBER OF BYTES
FNAME	FILE NAME SAME AS FILE IDENTIFIER OF DIRECTORY RECORD	15 BYTES
reserved	RESERVED	1 BYTE
BN	BOOK NUMBER OF THIS STANDARD	1 BYTE
VERS	REVISION NUMBER OF EACH BOOK NUMBER	1 BYTE
VEND	VENDER IDENTIFIER OF UNIQUE NUMBER DESIGNATED FOR EACH VENDER	2 BYTES
NVOL	VOLUME NUMBER OF ANY NUMBER DESIGNATED BY DISC PROVIDER	1 BYTES
reserved	RESERVED	15 BYTES
NCHAIN	NUMBER OF TOTAL PROGRAM CHAINS IN THIS FILE	1 BYTES
NPROG	NUMBER OF TOTAL PROGRAMS IN THIS FILE	1 BYTES
NCELL	NUMBER OF TOTAL PROGRAM CELLS IN THIS FILE	2 BYTES
NDUT	NUMBER OF TOTAL DUTS IN THIS FILE	4 BYTES
NSECT	NUMBER OF TOTAL SECTORS IN THIS FILE	4 BYTES
reserved	RESERVED	20 BYTES
PCHAINIT	POINTER TO CHAINIT BLOCK IN THIS FILE	2 BYTES (NUMBER OF RELATIVE SECTORS)
PCELLIT	POINTER TO CELLIT BLOCK IN THIS FILE	2 BYTES (NUMBER OF RELATIVE SECTORS)
PDAT	POINTER TO DAT BLOCK IN THIS FILE	2 BYTES (NUMBER OF RELATIVE SECTORS)
reserved	RESERVED	10 BYTES
PCHAINIT	POINTER TO CHAINIT BLOCK IN THIS FILE (FOR DUPLEX WRITING)	2 BYTES (NUMBER OF RELATIVE SECTORS)
PCELLIT	POINTER TO CELLIT BLOCK IN THIS FILE (FOR DUPLEX WRITING)	2 BYTES (NUMBER OF RELATIVE SECTORS)
PDAT	POINTER TO DAT BLOCK IN THIS FILE (FOR DUPLEX WRITING)	2 BYTES (NUMBER OF RELATIVE SECTORS)
reserved	RESERVED	10 BYTES
UDER	USER DEFINITION REGION	928 BYTES OR MORE

FILE MANAGEMENT TABLE (FMT)

FIG.17

PARAMETER	DESCRIPTION	NUMBER OF BYTES
LCHAINIT	TOTAL LENGTH OF CHAINIT REPRESENTED IN BYTES	2 BYTES
CHAINMODE	MODE FOR ENTIRE CHAINS	2 BYTES
reserved	RESERVED	1 BYTE
NPROG	NUMBER OF PROGRAMS COMPOSING THIS PROGRAM CHAIN	1 BYTE
NCELL	NUMBER OF PROGRAM CELLS COMPOSING THIS PROGRAM CHAIN	2 BYTES
NDUT	NUMBER OF DATA UNITS COMPOSING THIS PROGRAM CHAIN	4 BYTES
NCHNL	NUMBER OF MAXIMUM CHANNELS OF SUB IMAGE USED IN THIS PROGRAM CHAIN	2 BYTES
NSTRM	NUMBER OF STREAMS OF AUDIO USED IN THIS PROGRAM CHAIN	1 BYTE
reserved	RESERVED	1 BYTE
ECMODE	ENCODING FORMAT IN THIS PROGRAM CHAIN	1 BYTE
VATR	VIDEO DATA ATTRIBUTE OF THIS PROGRAM CHAIN	3 BYTES
CPLET	SUB IMAGE COLOR PALETTE IN THIS PROGRAM CHAIN	4 BYTES × 16
SPATR	CHANNEL ATTRIBUTE OF EACH SUB IMAGE IN THIS PROGRAM CHAIN : <div style="text-align: center;"> b15 b14 b13 b12 b11 74 b8 <div style="display: flex; justify-content: space-around; border: 1px solid black; margin: 2px;"> RESOLUTION ASPECT TYPE </div> b7 b0 <div style="display: flex; justify-content: space-around; border: 1px solid black; margin: 2px;"> SPECIFIC CODE </div> </div> • RESOLUTION = 00 : FIELD RECORD 01 : FRAME RECORDING • ASPECT = 00 : 4 TO 3 DISPLAY 01 : 16 TO 9 DISPLAY • TYPE = 0000 : LANGUAGE • SPECIFIC CODE = IN THE CASE OF TYPE (0000 : LANGUAGE), IT IS DESIGNATED CORRESPONDING TO LANGUAGE CODE. OTHER TYPES ARE RESERVED.	2 BYTES × NCHNL

FIG.18

PARAMETER	DESCRIPTION	NUMBER OF BYTES
AATR	AUDIO ATTRIBUTE OF EACH STREAM IN THIS PROGRAM CHAIN	2 BYTES × NSTRM
reserved	RESERVED	1 BYTE
NBP	NUMBER OF BRANCH POINTS IN THIS PROGRAM CHAIN	1 BYTE
BINFO	GROUP OF PROGRAM CELL NUMBERS SHARED WITH OTHER PROGRAM CHAINS	2 BYTES × NBP
SCINFO	<p>REPRODUCTION ORDER OF PROGRAM CELLS COMPOSING THIS PROGRAM CHAIN WRITTEN FOR NUMBER OF PROGRAM CELLS</p> <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <div style="display: flex; justify-content: space-between; font-size: small;"> b31b30 b29 b26 b2772b24 </div> <div style="display: flex; justify-content: space-between;"> REPRODUCTION CONTROLANGLE MODEANGLE NUMBER </div> </div> <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <div style="display: flex; justify-content: space-between; font-size: small;"> b2371b16 </div> <div style="text-align: center;">PROGRAM NUMBER</div> </div> <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <div style="display: flex; justify-content: space-between; font-size: small;"> b15b8 </div> <div style="text-align: center;">HIGH ORDER OF PROGRAM CELL NUMBER</div> </div> <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <div style="display: flex; justify-content: space-between; font-size: small;"> b7b0 </div> <div style="text-align: center;">LOW ORDER OF PROGRAM CELL NUMBER</div> </div> <p>• REPRODUCTION CONTROL = 00: SUCCESSIVELY ADVANCES TO NEXT PROGRAM (PRESENCE OF CONTINUITY BETWEEN PROGRAMS) 01: SUCCESSIVELY ADVANCES TO NEXT PROGRAM (ABSENCE OF CONTINUITY BETWEEN PROGRAMS) 10: ADVANCES TO NEXT PROGRAM AFTER REPRODUCTION OF THIS PROGRAM WITH WAITING TIME DESIGNATED BY CELLIT. 11: STOPS AFTER REPRODUCTION OF THIS PROGRAM</p> <p>• ANGLE MODE = 00: NO ANGLE BLOCK 01: RESERVED 10: START/CONTINUANCE OF ANGLE BLOCK 11: END OF ANGLE BLOCK</p> <p>• ANGLE NUMBER = xxxx: NUMBER IN ANGLE BLOCKS (DESIGNATES SERIAL NUMBER FROM START OF ANGLE BLOCKS. * 0000: DEFAULT REPRODUCTION)</p> <p>• PROGRAM NUMBER = PROGRAM NUMBER OF PROGRAM CELL</p> <p>• PROGRAM CELL NUMBER = PROGRAM CELL NUMBER TO BE REPRODUCED (2 BYTES)</p>	4 BYTES × NCELL

FIG.19

PARAMETER	DESCRIPTION	NUMBER OF BYTES
CELLMODE	DESIGNATES CELL MODE	2 BYTES
PWAIT	WAIT TIME IN THE CASE THAT WAIT CONTROL IS DESIGNATED BY SCINFO IN CHAINIT. (FROM 0 TO 255 SECONDS)	1 BYTE
PRGNO	PROGRAM NUMBER OF THIS PROGRAM CELL	1 BYTE
SDUT	FIRST NUMBER OF DUT COMPOSING THIS PROGRAM CELL	4 BYTES
NDUT	NUMBER OF TOTAL DUTS COMPOSING THIS PROGRAM CELL	2 BYTES
SADUT	FIRST SECTOR POSITION OF FIRST DUT COMPOSING THIS PROGRAM CELL (REPRESENTED BY NUMBER OF RELATIVE SECTORS FROM TOP OF FILE)	4 BYTES
EADUT	FIRST SECTOR POSITION OF LAST DUT COMPOSING THIS PROGRAM CELL (REPRESENTED BY NUMBER OF RELATIVE SECTORS FROM TOP OF FILE)	4 BYTES


PROGRAM CELL INFORMATION TABLE (CELLIT)

FIG.20

PARAMETER	DESCRIPTION	NUMBER OF BYTES
TSADR	POSITION OF DUT REPRESENTED BY NUMBER OF RELATIVE SECTORS FROM TOP OF FILE	4 BYTES

DATA UNIT POSITION TABLE (DAT)

FIG.21



EXAMPLE OF PROGRAM CHAIN SELECTING PROCESS

FIG.22




FIG.23

BRANCH NUMBER	SHARED PROGRAM CELL NUMBER (2 BYTES)
0	0001h
1	0002h
2	0003h

BRANCH INFORMATION OF CHAIN (A) (BINFO)

BRANCH NUMBER	SHARED PROGRAM CELL NUMBER (2 BYTES)
0	0001h
1	0002h

BRANCH INFORMATION OF CHAIN (B) (BINFO)

BRANCH NUMBER	SHARED PROGRAM CELL NUMBER (2 BYTES)
0	0003h

BRANCH INFORMATION OF CHAIN (C) (BINFO)

FIG.24

NOTE) x = DON'T CARE

NUMBER	REPRODUCTION CONTROL (2 BITS)	ANGLE MODE (2 BITS)	ANGLE NUMBER (4 BITS)	PROGRAM NUMBER (1 BYTE)	PROGRAM CELL NUMBER (2 BYTES)	REMARKS
0	00	00	xxxx	00h	0000h	SHARED
1	00	00	xxxx	01h	0001h	SHARED
2	00	00	xxxx	01h	0002h	SHARED
3	00	00	xxxx	01h	0003h	SHARED
4	11	00	xxxx	02h	0004h	

BRANCH INFORMATION OF CHAIN (A) (SCINFO)

NOTE) x = DON'T CARE

NUMBER	REPRODUCTION CONTROL (2 BITS)	ANGLE MODE (2 BITS)	ANGLE NUMBER (4 BITS)	PROGRAM NUMBER (1 BYTE)	PROGRAM CELL NUMBER (2 BYTES)	REMARKS
0	00	00	xxxx	00h	0005h	SHARED
1	00	00	xxxx	00h	0001h	SHARED
2	00	00	xxxx	00h	0002h	
3	11	00	xxxx	00h	0006h	

BRANCH INFORMATION OF CHAIN (B) (SCINFO)

NOTE) x = DON'T CARE

NUMBER	REPRODUCTION CONTROL (2 BITS)	ANGLE MODE (2 BITS)	ANGLE NUMBER (4 BITS)	PROGRAM NUMBER (1 BYTE)	PROGRAM CELL NUMBER (2 BYTES)	REMARKS
0	00	00	xxxx	00h	0007h	SHARED
1	00	00	xxxx	00h	0003h	
2	11	00	xxxx	00h	0008h	

BRANCH INFORMATION OF CHAIN (C) (SCINFO)

FIG.25




FIG.26


61

NOTE) x = DON'T CARE

NUMBER	REPRODUCTION CONTROL (2 BITS)	ANGLE MODE (2 BITS)	ANGLE NUMBER (4 BITS)	PROGRAM NUMBER (1 BYTE)	PROGRAM CELL NUMBER (2 BYTES)	REMARKS
0	00	00	xxxx	01h	0000h	
1	01	00	xxxx	01h	0001h	
2	00	00	xxxx	01h	0004h	
3	10	00	xxxx	01h	0002h	
4	11	00	xxxx	01h	0003h	

CONTROL INFORMATION 1 OF PROGRAM CHAIN (SCINFO)

FIG.27



EXAMPLE 1 OF REPRODUCTION CONTROL OF PROGRAM CHAIN
 * NO MULTI-ANGLE (ANGLE MODE = 00B)

FIG.28




FIG.29

61 71 72


S S S

NOTE) x = DON' T CARE

NUMBER	REPRODUCTION CONTROL (2 BITS)	ANGLE MODE (2 BITS)	ANGLE NUMBER (4 BITS)	PROGRAM NUMBER (1 BYTE)	PROGRAM CELL NUMBER (2 BYTES)	REMARKS
0	00	00	xxxx	01h	0000h	DESIGNATED
1	00	10	0000	01h	0001h	
2	00	10	0001	01h	0005h	
3	00	11	0002	01h	0006h	
4	00	00	xxxx	01h	0002h	
5	00	10	0000	01h	0003h	
6	00	11	0001	01h	0007h	
7	11	00	xxxx	01h	0004h	

CONTROL INFORMATION 2 OF PROGRAM CHAIN (SCINFO)

FIG.30



EXAMPLE 2 OF PROGRAM CHAIN REPRODUCTION CONTROL
 * PRESENCE OF MULTI-ANGLE (ANGLE MODE = 10B OR 11B)

FIG.31





FIG.32




- REPRODUCTION CONTROL...
 - 00 : SUCCESSIVELY ADVANCES TO NEXT CELL
 - 01 : RESERVED
 - 10 : PAUSE
 - 11 : END OF SEQUENCE
- BLOCK MODE ...
 - 00 : NO BLOCK CELL
 - 01 : TOP BLOCK CELL
 - 10 : BLOCK CELL EXCEPT TOP CELL AND END CELL
 - 11 : END BLOCK CELL
- BLOCK TYPE ...
 - 0000 : NO BLOCK
 - 0001 : ANGLE BLOCK
 - 0010 : MENU BLOCK
 - OTHERS : RESERVED
- CELL NUMBER ... 2 BYTES

FIG.33

PARAMETER	DESCRIPTION	NUMBER OF BYTES
CCAT	CELL TYPE	2 BYTES
CTIME	TOTAL TIME OF CELLS	4 BYTES
CSADUT	TOP ADDRESS OF CELLS	4 BYTES
CEADUT	END ADDRESS OF CELLS	4 BYTES

[CCAT] PARAMETER



- CELL TYPE ...
- 0000 : MOVIE
 - 0001 : ORCHESTRAL MUSIC PROGRAM
 - 1000 : FILE SELECTING MENU
 - 1001 : SEQUENCE SELECTING MENU
 - 1010 : AUDIO STREAM SELECTING MENU
 - 1011 : SUB VIDEO CHANNEL SELECTING MENU
 - 1100 : PROGRAM SELECTING MENU
 - 1101 : ANGLE SELECTING MENU
 - OTHERS : RESERVED
- SPECIFIC CODE ... WHEN CELL TYPE IS MENU. LANGUAGE CODE IS WRITTEN.

FIG.34




FIG.35




FIG.36




FIG.37




FIG.38




FIG.39

CELL NUMBER	SPECIFIC CODE	BLOCK TYPE	BLOCK MODE
0	JAPANESE	MENU	BLOCK START
1	JAPANESE	MENU	BLOCK REGION
2	ENGLISH	MENU	BLOCK REGION
3	ENGLISH	MENU	BLOCK END

FIG.40




FIG.41

